



QUARRY ORIGIN

Quarried in Onaway and Sault Ste. Marie, Michigan. Cut and processed at our mill in Howard City, Michigan.

APPLICATION

Exterior and interior veneer. Available in thin veneer with corners. This blend is not produced in full-bed depth.

ALSO CUT AS

Huron Field Ledge
Huron Ledge

Please note: the beauty of natural stone is in its variety and range of color. Small pictures and samples are not fully representative. We do not recommend making a selection based on pictures alone — request a physical sample.

ASHLAR CUT

Huron

STONE TYPE	90% Dolomite limestone, 10% Soo Lock Sandstone		
COLOR	90% various shades of gray and buff, 10% various shades of red, with a range of molted to solid in color		
HEIGHT	4-8 inches (average of 6 inches)		
LENGTH	6-20 inches (average of 12 inches)		
NOMINAL THICKNESS	THIN VENEER	.5-1.5 inches	
APPROX. COVERAGE	THIN VENEER	10-14 pounds/square foot	
CORNER RETURNS	Varies in length of return, minimum of 3 inches		

TYPICAL PIECE

Rough-cut stone with a natural cleft top and bottom. Face of stone is a mixture of split and seam face. Ends are random and not trimmed. Backs are sawn for thin veneer. Not available in full-bed depth.

Hold it before you decide.

Request a physical sample of this blend and cut.

(616) 835-5289 · [THESTONEMILLINC.COM/CONTACT](https://www.thestonemillinc.com/contact)

THE STONE MILL INC.

20315 W. Edgar Rd, Howard City, Michigan 49329
(616) 835-5289 · [thestonemillinc.com](https://www.thestonemillinc.com)

HURON · ASHLAR

Issued August 2026 · supersedes all prior sheets
Data subject to natural variation